## DOBLE ACCESSORIES COMPACT AC CURRENT CLAMP

High Accuracy Voltage Output Current Clamp

## CAPTURE CURRENT READINGS FOR CIRCUIT BREAKER AND PROTECTION TESTING

Doble's Compact AC Current Clamp is designed to help you perform precise protection or circuit breaker testing in tight wiring circuits. This highly accurate current probe is used with your Doble F-Series test instruments (and the F6820 AIM option) for monitoring and recording parameters or Doble TDR circuit breaker test instruments. Its "clothes pin" shape makes it ideal for testing in and around control panels, cabinets and outlets.

## **TECHNICAL SPECIFICATIONS**



Current Range	1mA to 10A AC, continuous
Output Signal	100mV AC/A AC (1V @ 10A)
Accuracy and Phase Shift	Reference conditions: 23°C $\pm$ 3°K, 20 to 85% RH, 48 to 65Hz, external magnetic field < 40A/m, no DC component, no external current- carrying conductor, test sample centered. Load impedance 1M $\Omega$
Accuracy	1mA to 10A: 2% ± 2mA 40Hz to 3kHz: 3.5% ± 2mA
Phase Shift	45 to 65Hz 100A to 10A: less than or equal to $8^\circ$
Overload	20A continuous
Frequency Range	30 to 5kHz
Load Impedance	100k <b>û</b> minimum
Working Voltage	250V AC
Common Mode Voltage	30V AC
	MECHANICAL SPECIFICATIONS
Operating Temperature	HECHANICAL SPECIFICATIONS -13° to 122° F (-25° to 50° C)
Temperature	-13° to 122° F (-25° to 50° C)
Temperature Storage Temperature Temperature	-13° to 122° F (-25° to 50° C) -40° to 176° F (-40° to 80° C)
Temperature Storage Temperature Temperature Influence	-13° to 122° F (-25° to 50° C) -40° to 176° F (-40° to 80° C) <0.2% per 10°K
Temperature Storage Temperature Temperature Influence Dimensions	-13° to 122° F (-25° to 50° C) -40° to 176° F (-40° to 80° C) <0.2% per 10°K 1.26 x 4.5 x 0.87 inch (32 x 115 x 22mm)
Temperature Storage Temperature Influence Dimensions Weight	-13° to 122° F (-25° to 50° C) -40° to 176° F (-40° to 80° C) <0.2% per 10°K 1.26 x 4.5 x 0.87 inch (32 x 115 x 22mm) 6oz (160g)
Temperature Storage Temperature Influence Dimensions Weight Colors Polycarbonate	-13° to 122° F (-25° to 50° C) -40° to 176° F (-40° to 80° C) <0.2% per 10°K 1.26 x 4.5 x 0.87 inch (32 x 115 x 22mm) 6oz (160g) Dark gray handles with red cover
Temperature Storage Temperature Influence Dimensions Weight Colors Polycarbonate material	-13° to 122° F (-25° to 50° C) -40° to 176° F (-40° to 80° C) <0.2% per 10°K 1.26 x 4.5 x 0.87 inch (32 x 115 x 22mm) 6oz (160g) Dark gray handles with red cover Handle: 10% fiberglass charged polycarbonate UL 94 VO

ELECTRICAL SPECIFICATIONS



Doble Engineering Company Worldwide Headquarters 85 Walnut Street, Watertown, MA 02472 USA tel +1 617 926 4900 | fax +1 617 926 0528 www.doble.com Specifications are subject to change without notice. Doble is ISO certified. Doble is an ESCO Technologies Company. MKT\_SL\_COMPACT\_AC\_CURRENT\_PROBE\_12/15